



MATERIAL IS 1/2" THICK TEMPERED GLASS WITH STEEL FRAME
FINISH IS GRAY POWDER COAT ON BRACKETS AND PLATES..

| | | |
|-----|-----|----------|
| G | ERD | 08-04-23 |
| F | MJP | 03/27/23 |
| E | MJP | 07/01/21 |
| D | JJC | 11/15/17 |
| C | RWP | 06/08/09 |
| B | RWP | 06/06/08 |
| A | JJC | 12/01/03 |
| REV | BY | DATE |



Gared Performance Sports Systems
9200 East 146th Street, Suite A
Noblesville, IN 46060

THIS DOCUMENT CONTAINS TRADE SECRET AND OTHER MATERIALS WHICH ARE PROTECTED BY CONFIDENTIALITY NOTICE AND AGREEMENT AND BY COPYRIGHT. ANY USE OR COPYING OF THIS DOCUMENT EXCEPT AS AUTHORIZED BY GARED PERFORMANCE SPORTS SYSTEMS IS STRICTLY PROHIBITED.

LXP4200 REC GLASS BACKBOARD

| | | | | | |
|--------------------|---------------|--------------------|---------------------|-------------|--|
| DRAWN CONNERLEY | | DATE 5/2/2003 | | DATE ISSUED | |
| APPROVED | | DATE | | | |
| SIZE A | SCALE NONE | SHT. NO. 1 OF 2 | PART NO. LXP4200 | REV G | |



MODEL LXP4200

STEEL FRAME 72" X 42" RECTANGULAR GLASS BACKBOARD

The LXP4200 backboard shall be fabricated with steel frame constructed of formed steel angles, former and fastened together and connected with heavy gauge steel mounting plates to reinforce corners. The lower horizontal frame section shall have a tubular steel support brace for added strength. Manufacturer of backboard shall have over ten years of experience producing such item. Backboard shall meet NCAA and high school requirements.

Entire frame and components shall be powder coated with a durable neutral gray finish. Acrylic cushioning pad shall be used between steel mounting plate and glass to protect board against possible breakage.

Glass shall be ½" in thickness and fully tempered with white target lines permanently fused onto the surface. Vinyl shock absorbing material insulates the glass from the frame. Goal mounting holes shall be on standard 5" horizontal and 4" vertical centers.

ACCESSORIES

GOALS

See Goal-Board Matrix specification sheet for goal compatibility.